

# AUTO SHUT OFF SCREWDRIVER



MODEL	FREE SPEED	CAPACITY	TORQUE RANGE	FROM CENTER TO OUTSIDE	OVERALL LENGTH	AIR HOSE ID	AVG. AIR CONS	WEIGHT
AT-33011-STUA	1100 RPM	5/32" (4MM)	1.1-2.1 NM ( 9.7-18.5 IN-LB)	15.5 MM(0.6")	187MM	1/4"	198MM (2.0 CFM)	0.43KG
AT-33017-STUA	1700 RPM	9/64" (3.5MM)	0.7-1.5NM ( 6.2-13.2 IN-LB)	15.5 MM(0.6")	187MM	1/4"	198MM (2.0 CFM)	0.43KG
AT-33023-STUA	2300 RPM	1/8" (3MM)	0.4-1 NM (3.5-8.8 IN-LB)	16.5MM(0.6")	187MM	1/4"	198MM (2.0 CFM)	0.43KG
AT-34008-STUA	800 RPM	13/64" (5mm)	1.6-4 NM ( 14.1-35.2 IN -LB)	16.5MM(0.6")	209MM	1/4"	297 L/MIN (10.5 CFM)	0.65KG
AT-34015-STUA	1500 RPM	5/32" ( 4mm)	1-2.2 NM ( 8.8-19.4 IN -LB)	16.5MM(0.6")	209MM	1/4"	297 L/MIN (10.5 CFM)	0.65KG
AT-35005-STUA	480 RPM	13/64-15/64 (5-6MM)	5-10.5NM ( 44-92.4 IN -LB)	19.5MM(0.8")	240MM	3/8"	496 L/MIN (17.5 CFM)	1.00KG
AT-35008-STUA	800 RPM	13/64-15/64 (5-6MM)	3-5.5 NM ( 26.4-48.4 IN -LB)	19.5MM(0.8")	240MM	3/8"	496 L/MIN (17.5 CFM)	1.00KG
AT-35017-STUA	1700 RPM	5/32-13/64 (4-5MM)	1.5-2.6 NM ( 13.2-23 IN -LB)	19.5MM(0.8")	240MM	3/8"	496 L/MIN (17.5 CFM)	1.00KG
AT-33011-SLUA	1100 RPM	9/64" (3.5mm)	1.1-2.1 NM (9.7-18.5 FT-LB)	15.5MM(0.6")	187MM	1/4"	198 L/MIN ( 7.0 CFM)	0.43KG
AT-33017-SLUA	1700 RPM	9/64" (3.5mm)	0.7-1.5 NM ( 6.2-13.2 FT-LB)	15.5MM(0.6")	198MM	1/4"	198 L/MIN ( 7.0 CFM)	0.43KG
AT-33023-SLUA	2300 RPM	1/8" (3MM)	0.4-1 NM ( 3.5-8.8 FT-LB)	15.5MM(0.6")	198MM	1/4"	198 L/MIN ( 7.0 CFM)	0.43KG
AT-34008-SLUA	800 RPM	13/64" (5MM)	1.6-4 NM (14.1-35.2 IN-LB)	16.5MM(0.6")	209MM	1/4"	297 L/MIN (10.5 CFM)	0.65KG
AT-34015-SLUA	1500 RPM	5/32" (4MM)	1-2.2 NM ( 26.4-48.4 IN-LB)	16.5MM(0.6")	209MM	1/4"	297 L/MIN (10.5 CFM)	0.65KG
AT-34021-STUA	2100 RPM	5/32" (4MM)	1-1.7 NM ( 8.8-13.2 IN -LB)	16.5MM(0.6")	209MM	1/4"	297 L/MIN (10.5 CFM)	0.65KG